AIRSCREEN DATA SHEET




THE NANO MODEL

The **nano** combines all the great features AIRSCREEN users know and love but is also as portable as never before. Weighing just 44b (20kg), the AIRSCREEN nano, is the perfect outdoor screen solution for garden parties, backyard cinema events and anything in between. The screen is an ideal size for up to 100 viewers and inflates in just 60 seconds.

COMPONENTS

- ► AIRSCREEN nano
 - Inflatable frame
 - ▶ Front or rear projection screen
 - Screen ties
 - Adjustable nylon tethers
 - Handheld blower
 - ▶ 2 year warranty
- Including all necessary equipment and manual


Compact and lightweight when deflated - yet surprisingly big when inflated!



Ideal for everyone who wants to set-up a small cinema easily & quickly! + Compact and lightweight

THE AIRTIGHT MODELS

The **airtight** models are available from 16ft (4.88m) to 24ft (7.32m) screen width and are built in a way that they do not require a blower during screen operation. The big advantage of this construction is the zero noise emitting operation of the screen e.g. for small audiences or indoor purposes. If some day a hole develops, a patented controlled blower box (optional) keeps your screen perfectly inflated when needed and switches off automatically once the pressure is right again.





THE CLASSIC MODELS

The **classic** model range covers sizes from 20ft (6.10m) all the way up to 52ft (16m) screen width. Permanent high pressure inflation and precise engineering result in a product which never let you down. Moreover it is designed to give you a number of options to adopt to different circumstances e.g. blower attachment points on both sides of the frame.


COMPONENTS For constant users who seek for the most reliable screening solution for different kind of uses! ► AIRSCREEN classic + Extremely durable Inflatable frame Front or rear projection screen + Rapid inflation and deflation Wrinkle free 2:1 screen surface with Screen ties black backside - no disturbing backlight! + Remains upright even with minor punctures Adjustable nylon tethers Permanently running blower ▶ 2 year warranty Including all necessary equipment and manual Ultra-solid frame due to hf-welding and reinforced details - this frame will never let vou down! Permanent inflation by high pressure blower rapid inflation and flawless performance! ARSCHEN 3 of 7

The AIRSCREEN Company · Hafenweg 26 · 48155 Münster · Germany +49 251 60 90 250 · info@airscreen.com · www.airscreen.com



SIZE OVERVIEW





* Height of person illustrated: 5.7ft (1.75m)

The AIRSCREEN Company · Hafenweg 26 · 48155 Münster · Germany +49 251 60 90 250 · info@airscreen.com · www.airscreen.com

TECHNICAL SPECIFICATIONS: $m \cdot kg \cdot km/h$



Model		nano	airtight	airtight	airtight	classic	classic	classic	classic	classic	
Screen surface	Size (m)	3.00 x 1.70	4.88 x 2.74	6.10 x 3.43	7.32 x 4.12	<mark>6.10 x 3.43</mark>	7.32 x 4.12	9.15 x 5.15	12.00 x 6.00	16.00 x 8.00	
	Rear projection size (m)	2.50 x 1.45	4.28 x 2.44	5.10 x 2.93	6.12 x 3.52	<mark>5.10 x 2.93</mark>	6.12 x 3.52	7.75 x 4.44	10.00 x 5.00	13.65 x 6.83	
	Material	PVC matt-white with black back side (front projection)									
	Gain factor	Front projection surface: 0.96, rear projection surface: 1.48									
	Height off the ground (m)	1.00	1.00 1.75						2.20	3.00	
	Rear projection possible										
	Weight (kg)	5	8	12	18	12	18	28	42	76	
Frame	Size (m)	3.5 x 2.9	5.5 x 4.8	7.1 x 5.7	8.5 x 6.5	<mark>7.1 x 5.7</mark>	8.5 x 6.5	10.6 x 7.9	14.0 x 9.2	18.4 x 12.2	
	Middle column	Νο									
	Eyelet row	Front (20 cm spacing)							Front and rear (20 cm spacing)		
	Weight (kg)	20	42	72	98	<mark>58</mark>	78	117	207	334	
Accessories	Belt length (m)	10	10	10	15	10	15	15	20	25	
	Belt width (mm)	25	25	25	25	25	25	35	50	50	
	No. of screen ties	70	100	125	145	<mark>125</mark>	145	180	290	380	
	Blower		Handheld (110	V AC or 220V AC)		Permanently running blower (110V AC or 220V AC)					
	Additional blower		Not p	oossible		Optional					
Others	Fire rating	DIN 2102 B1									
	Wind rating (km/h)	<mark>38</mark>									
	Footprint (m)*	6 x 6	9 x 10	12 x 11	14 x 13	<mark>12 x 11</mark>	14 x 13	17 x 16	22 x 18	28 x 24	
hann may irod for or	Shipping dimensions (cm) peration (width x depth)	1 pallet (120 x 80 x 70)					1 pallet (120 x 80 x 125)	2 pallets (120 x 100 x 120) (120 x 80 x 125) 5 c			

The AIRSCREEN Company · Hafenweg 26 · 48155 Münster · Germany

+49 251 60 90 250 · info@airscreen.com · www.airscreen.com

TECHNICAL SPECIFICATIONS: ft \cdot lb \cdot mph



Model		nano	airtight	airtight	airtight	classic	classic	classic	classic	classic	
Screen surface	Size (ft)	10 x 5.5	16 x 9	20 x 11.25	24 x 13.5	<mark>20 x 11.25</mark>	24 x 13.5	30 x 17	40 x 20	52 x 26	
	Material				PVC matt-white v	with black back sid	<mark>e (front projection)</mark>)			
	Gain factor	Front projection surface: 0.96, rear projection surface: 1.48									
	Height off the ground (lb)	3.28 <u>5.75</u> 6.56							7.22	9.84	
	Rear projection possible	ole (Yes)									
	Weight (Ib)	11	18	27	40	27	40	62	93	168	
Frame	Size (ft)	11.5 x 9.5	18.0 x 15.7	23.3 x 18.7	27.9 x 21.3	23.3 x 18.7	27.9 x 21.3	34.8 x 25.9	45.9 x 30.2	60.4 x 40.0	
	Middle column	No									
	Eyelet row	Front (7.89 in spacing)							Front and rear	Front and rear (7.89 in spacing)	
	Weight (Ib)	44	93	159	216	<mark>128</mark>	172	258	456	736	
Accessories	Belt length (m)	33	33	33	49	33	49	49	66	82	
	Belt width (mm)	1	1	1	1	1	1	1.4	1.4	2	
	No. of screen ties	70	100	125	145	125	145	180	290	380	
	Blower		Handheld (110)	V AC or 220V AC)		Permanently running blower (110V AC or 220V AC)					
	Additional blower		Not p	oossible		Optional					
Others	Fire rating	DIN 2102 B1									
	Wind rating (mph)	<mark>24</mark> ,									
	Footprint (ft)*	20 x 20	30 x 33	39 x 36	46 x 43	<mark>39 x 36</mark>	46 x 43	56 x 53	72 x 59	92 x 79	
	Shipping dimensions (in)	1 pallet (47 x 31 x 28)				1 pallet (47 x 31 x 49)			2 pallets (47 x 39 x 49) (47 x 31 x 49) 6 of		

The AIRSCREEN Company · Hafenweg 26 · 48155 Münster · Germany

+49 251 60 90 250 · info@airscreen.com · www.airscreen.com

AIRSCREEN - THE ULTIMATE INFLATABLE MOVIE SCREEN





Worldwide shipping - customers in over 110 countries



Global network a service partner near to you



Proven quality two years warranty & security certificates



24h service hotline - we are there when you need us



Worldwide services our technicians go everywhere



Extensive stock - rapid delivery of products & spare parts