

VSC 500

HIGH RESOLUTION COMPUTER-TO-VIDEO SCAN CONVERTER

- One VGA input with buffered loop-through
- Three simultaneous outputs:
 - Composite video
 - S-video
 - Component or RGB video
- Autoscanning up to 1600x1200
- Auto-Image™ setup
- Four vertical filters for improved image clarity
- Sizing & centering controls
- Zoom control with eight presets
- 60 factory and 16 user-accessible auto memory location presets
- Freeze function captures a frame of video for extended display
- Internal color bar generator
- RS-232/RS-422 remote control
- Optional IR remote control



The Extron VSC 500 is a single input, high resolution computer-to-video scan converter that combines high performance, essential features, and value. It is ideal for everyday use in videoconference facilities, conference rooms and boardrooms, and for recording the output of a computer as an NTSC or PAL video signal.



Extron® Electronics

www.extron.com

DESCRIPTION

The Extron VSC 500 High Resolution Computer-to-Video Scan Converter combines high performance processing, features, and value. It accepts computer-video signals at resolutions up to 1600x1200 and simultaneously outputs a scan-converted video signal as NTSC or PAL composite video, S-video, and component video or RGB video. The VSC 500 is ideal for everyday use in a wide range of applications including videoconferencing, video recording, and viewing of computer-video images on an NTSC or PAL monitor or other video display device.

The VSC 500 features Auto-Image setup for automatic adjustment of centering, sizing, and filter settings. Additional key features include zoom control up to 200%, a color bar generator, an LCD display for user-friendly menu navigation, memory presets, and a buffered loop-through for local monitor output.

The VSC 500 can be controlled via the front panel, RS-232 or RS-422 serial control, or the optional VSC Remote handheld IR remote control. It is housed in a rack-mountable 1U, half rack width enclosure and is equipped with an internal international power supply.

FEATURES

- **Automatically recognizes and converts computer resolutions from 560x384 to 1600x1200 and frequencies to 100 kHz horizontal and 120 Hz vertical**
- **Buffered loop-through** – Provides a local monitor output, enabling the computer input signal to be monitored without the need for a separate distribution amplifier.
- **Three simultaneous outputs** – NTSC or PAL standard video is output as composite video, S-video, and component or RGB video.
- **Auto-Image setup** – Saves time by providing calibration of image size, position, clock, and phase adjustments at the touch of a button.
- **Vertical filtering** – Four selectable vertical filters reduce jitter, improve image quality, and help maintain picture detail.
- **Sizing and centering controls** – User-friendly positioning is accessible through the front panel for quick and efficient image setup.
- **Image zoom control and presets** – Eight zoom presets are available for recalling size, position, and filtering, enabling the user to quickly zoom in on a certain area of an image.
- **Input memory presets** – Allow the scan converter to automatically recall up to 16 user presets, 60 factory presets, and eight zoom presets. Each memory location stores filter, size, and centering, or zoom settings for each source which can be recalled instantaneously when switching between different computer-video inputs and resolutions.
- **Image freeze control** – The output video can be frozen using the freeze button on the front panel. This allows the scan converter to capture a frame of video to display for an extended period of time, even after the source has been removed.

FEATURES - Cont.

- **Internal color bar generator** – An internally-generated color bar pattern is provided for simplified setup of a display. The color bar pattern or a black screen can also be set as the default output when no input signal is present.
- **RS-232 and RS-422 serial control port** – Using serial commands, the VSC 500 can be controlled and configured via the Extron Windows®-based control program, or integrated into third-party control systems. Extron products use the SIS™ - Simple Instruction Set command protocol, a set of basic ASCII code commands that allow for quick and easy programming.
- **Optional IR remote control, part # 70-206-01** – The optional VSC Remote handheld IR remote control performs most front panel functions such as image freeze, zoom in and out, size and shift, vertical filter adjustment, and preset selection.
- **Front panel security lockout** – This feature locks out all front panel functions except for input selection; all functions however, are available through RS-232 control.
- **Rack-mountable 1U, half rack width metal enclosure**
- **Internal international power supply** – The 100-240VAC, 50/60 Hz, autoswitchable internal power supply provides worldwide power compatibility.

ALSO AVAILABLE

The Extron VSC 700 High Resolution Computer-to-Video Scan Converter builds on the performance and features of the VSC 500, incorporating RGBHV input on BNCs with a buffered loop-through that simplifies integration, as well as additional filter adjustments for fine-tuning image quality. The VSC 700 is also available with SDI - Serial Digital Interface output and includes video genlock, enabling integration into broadcast and production applications.

For enhanced integration requirements, the Extron VSC 900D Two Input High Resolution Computer-to-Video Scan Converter with Genlock and SDI Output includes two RGBHV inputs on BNCs and 15-pin HD, each with a buffered loop-through. In addition to SDI output and video genlock, the VSC 900D offers even more filter adjustment capability to further refine image quality.



Optional VSC Remote
Handheld IR Remote
Control

| VIDEO INPUT | |
|-----------------------------|---|
| Number/signal type | 1 RGBHV, RGBS, RGB with 1 buffered loop-through |
| Connectors | (1) 15-pin HD for input, (1) 15-pin HD for loop-through |
| Nominal level..... | 0.7 Vp-p for RGB |
| Minimum/maximum levels..... | 0 V to 2.0 Vp-p with no offset at unity gain |
| Impedance..... | 75 ohms |
| Horizontal frequency..... | Autoscan 24 kHz to 100 kHz |
| Vertical frequency..... | Autoscan 50 Hz to 120 Hz |
| Resolution range | Autoscan 560 x 384 to 1600 x 1200 |
| Maximum DC offset..... | 2.0 V |

| VIDEO PROCESSING | |
|----------------------------|--------------------------|
| Encoder | 10 bit digital |
| Digital sampling..... | 24 bit, 8 bits per color |
| Colors | 16.8 million |
| Horizontal filtering | 1 fixed level |
| Flicker filtering..... | 3 levels (selectable) |
| Encoder filtering..... | 4 levels |

| VIDEO OUTPUT | |
|-----------------------------|--|
| Number/signal type | 1 RGBHV, RGBS, RGB, or component video 1 S-video, 1 composite video (NTSC 15.75 kHz, 525 lines; or PAL, 15.5 kHz, 625 lines) |
| Connectors | 5 BNC female: RGBHV/RGBS/RGBS/ component video (1) 4-pin mini-DIN female: S-video 1 BNC female: NTSC/PAL composite video |
| Nominal level..... | 0.7 Vp-p for RGB |
| Minimum/maximum levels..... | 0.0 V to 1.0 Vp-p |
| Impedance..... | 75 ohms |

| SYNC | |
|------------------------|-----------------------------|
| Input type | Autodetect RGBHV, RGBS, RGB |
| Output type..... | RGBHV, RGBS, RGB |
| Standards..... | NTSC 3.58, PAL |
| Input level | 1.5 V to 5.0 Vp-p |
| Output level..... | TTL: 5.0 Vp-p, unterminated |
| Input impedance..... | 600 ohms |
| Output impedance..... | 75 ohms |
| Max input voltage..... | 5.0 Vp-p |
| Polarity..... | Negative |

| CONTROL/REMOTE — SCAN CONVERTER | |
|--|--|
| Serial control port | RS-232 or RS-422, 9-pin female D connector |
| Baud rate and protocol | 9600 baud, 8 data bits, 1 stop bit, no parity |
| Serial control pin configurations..... | 2 = TX, 3 = RX, 5 = GND, 9 = hard-wired IR |
| IR controller module..... | VSC Remote |
| Program control..... | Extron's control/configuration program for Windows® Extron's Simple Instruction Set (SIS™) |

| GENERAL | |
|--|--|
| Power | 100VAC to 240VAC, 50/60 Hz, 40 watts, internal, autoswitchable |
| Temperature/humidity | Storage -40° to +158°F (-40° to +70°C) / 10% to 90%, noncondensing Operating +32° to +122°F (0° to +50°C) / 10% to 90%, noncondensing |
| Rack mount..... | Yes, with optional rack shelf, part #60-190-01 or 60-604-01 |
| Enclosure type..... | Metal |
| Enclosure dimensions | 1.75" H x 8.75" W x 10.5" D (1U high, half rack wide) 4.4 cm H x 22.2 cm W x 26.7 cm D (Depth excludes knobs.) |
| Product weight | 2.4 lbs (1.1 kg) |
| Shipping weight..... | 7 lbs (4 kg) |
| Vibration | ISTA/NSTA 1A in carton (International Safe Transit Association) |
| Listings..... | UL, CUL |
| Compliances | CE, FCC Class A, VCCI, AS/NZS, ICES |
| MTBF | 30,000 hours |
| Warranty..... | 3 years parts and labor |
| NOTE: All nominal levels are at ±10%. | |


| Model | Version Description | Part Number |
|---------|---------------------|-------------|
| VSC 500 | Scan Converter..... | 60-476-01 |

| Included Accessories | | |
|-----------------------------|--|-----------|
| VGA M-M MD/6 | Male to Male VGA Molded Connector Cable, 6' | 26-238-01 |
| MHR-2 SVM-F/6 | Male to Female 4-pin Mini DIN S-Video Cable, 6' | 26-542-02 |
| MHR-5 BNC/6 | BNC Male to Male Five Conductor MHR - Mini High Resolution Cable, 6' | 26-260-01 |


| Optional Accessories | | |
|-----------------------------|--|------------|
| VSC Remote | Handheld IR Remote Control for VSC Series.... | 70-206-01 |
| RSU 129 | 1U 9.5" Deep Universal Rack Shelf Kit..... | 60-190-01 |
| MBU 129 | 1U, 1/2 Rack Width Under-Desk Mount Kit for Four-Piece Enclosure | 70-219-01 |
| RCAF-BNCM/10 | RCA Female-BNC Male, Qty. 10..... | 100-229-01 |
| SVHSM-BNCF 8" (20 cm) | S-Video Male to 2 BNC Female Adapter, 8" | 26-353-01 |
| MHR-2 SVM-M/6 | 4-pin Mini DIN Male-Male, 6' (1.8 m) | 26-316-02 |

Specifications are subject to change without notice.


APPLICATION DIAGRAM



PANEL DRAWINGS



Front



Back



Extron Electronics, USA
1230 South Lewis Street
Anaheim, CA 92805
800.633.9876 714.491.1500
FAX 714.491.1517

Extron Electronics, Europe
Beeldschermweg 6C
3821 AH Amersfoort, The Netherlands
+800.3987.6673 +31.33.453.4040
FAX +31.33.453.4050

Extron Electronics, Asia
135 Joo Seng Rd. #04-01
PM Industrial Bldg., Singapore 368363
+800.7339.8766 +65.6383.4400
FAX +65.6383.4664

Extron Electronics, Japan
Kyodo Building, 16 Ichibancho
Chiyoda-ku, Tokyo 102-0082
Japan
+81.3.3511.7655 FAX +81.3.3511.7656