

[Sign In / Shop](#) [Support / Training](#)
Main Site - Top Header

[Sign In / Shop](#) [Support / Training](#)
Main Site - Top Header



[Our Markets](#)

[Our Products](#)

[News & Events](#)

LCD Technical Specifications

[Company](#) [Request Demo](#) [Contact Sales](#)

Size & Weight

- Height: 3.3 inches (83.8 mm)
- Width: 2.1 inches (53.3 mm)
- Depth: 0.3 inches (7.6 mm)
- Weight: 1.0 ounce (28.4 grams)*

Range

- 200 ft. range (400 ft. coverage)

Battery & Power

- Two coin cell CR2032 (3.0V) lithium batteries
- Deep sleep mode when not in use
- Average battery life is 6 to 12 months

Input Device Capability

- 12 Keys (1/A – 10/J, Ch/Channel, ?)
- Answer Key – answers automatically transmitted
- Programmable – manually enter new ID number
- ResponseCard Programmer compatible

User Identification

- Select a channel in less than five seconds, indicating session choice
- Select a channel anytime – even when a session is underway
- Channel selection is preserved until changed by participant

Display



RF LCD electronic clicker screen

LCD Viewable Screen

Height: 0.4 inches (





Indicators: Company

[Request Demo](#) [Confirmation](#) [Contact Sales](#)

- Channel setting
- Battery life

LED Light

- Green Light – Response Confirmation (Three seconds)
- Red Light – Response Unconfirmed

RF Technology

- 82 channels can be running at once in close proximity
- Fully FCC, CE and Industry Canada certified
- Will not interfere with other technologies

*Weight is calculated with the addition of two coin cell CR2032 (3.0V) lithium batteries

[View Hardware Warranty.](#)

 [Sign In / Shop](#)

[Support / Training](#)

 [Sign In / Shop](#)

[Support / Training](#)



[Our Markets](#)

[Our Products](#)

[News & Events](#)

OH 44503
1.866.746.3015

[Company](#)

[Downloads](#)
[Request Demo](#)

[Support](#)
[Contact Sales](#)



© 2018 Turning Technologies, LLC. All Rights Reserved

[Privacy Policy](#) • [Terms of Use](#) • [Status Updates](#) • [Accessibility](#) • [Turning Foundation](#)