

DT 2 / DT 3

Dynamic Headphones



DT 2



DT 3

FEATURES

- Rugged construction
- Easy to clean
- Ergonomic design
- With mini stereo jack plug (3.5 mm)

APPLICATIONS

The lightweight DT 2 and DT 3 headphones are available in different versions and can be used in mobile applications with a tour guide system (cable length 0.8 m) or permanent applications of conferencing and interpreting systems (cable length 1.6 m). The ergonomic headphones in a modern design feature a high comfort and rugged construction. The matt non-glare surface prevents disturbing light reflections. After each guided tour or meeting the headphones can easily be cleaned.

VERSIONS

- DT 2 Headphone, 2 x 32 Ω , mini stereo jack 3.5 mm, cable length 0.8 m, for tour guide receiver. Order # 484.679
- DT 2 same as above, but cable length 1.6 m Order # 484.687
- DT 3 Neckworn headphone, 2 x 32 Ω , stereo jack 3.5 mm, cable length 0.8 m, for tour guide receiver. Order # 484.571
- DT 3 same as above, but cable length 1.6 m Order # 484.598

SPARE PARTS

- EDT 2 F 5 pairs of ear pads made of foam material, for DT 2 Order # 971.453
- EDT 3 F 5 pairs of ear pads made of foam material, for DT 3 Order # 901.555

TECHNICAL SPECIFICATIONS

Type	DT 2	DT 3
Transducer type	Dynamic	Dynamic
Operating principle	Open	Open
Frequency response	40 - 20,000 Hz	40 - 20,000 Hz
Nominal impedance	2 x 32 Ω	2 x 32 Ω
Nominal SPL	104 dB	104 dB
Power handling capacity	100 mW	100 mW
Weight without cable	39 g	45 g
Connection	Stereo jack plug 3.5 mm	Stereo jack plug 3.5 mm